



## HPBC solar panel 150W 12V

### Electrical characteristics

SKU	1180150
Maximum Power (Pmax)	150Wp
Voltage at Pmax (Vmp)	22.51V
Current at Pmax (Imp)	6.66A
Open-circuit Voltage (Voc)	26.99V
Short-circuit Current (Isc)	6.98A
Temperature coefficient of Voc	-0.270%/°C
Temperature coefficient of Isc	+0.048%/°C
Temperature coefficient of Power	-0.350%/°C
Normal operating cell Temperature	45 ± 2°C
Operating Temperature	-40 ~ +85°C
Maximum System Voltage	1000 VDC
Power Tolerance	0 ~ +3%
Junction box	IP67
Bypass diodes	3 pcs
Solar Cell	Mono 36 (3 × 12)
Connection cable and connector	4mm <sup>2</sup> x 90cm, Solar Stecker (+/-)
Performance guarantee	25 years
Dimension (mm)	1200 × 580 × 30
Weight (kg)	7.84




### Module diagram and characteristic curve




- HPBC solar cells
- 22.7% cell efficiency
- +3% Plus Tolerance Sorted
- reinforced aluminum frame
- TÜV Saar certified
- 25-year Product guarantee

I-V characteristics at different irradiances



I-V characteristics at different temperatures



\*Measured at standard test conditions: irradiance 1.000W/m<sup>2</sup>, air mass 1.5 spectrum, temperature 25°C  
Electrical parameters may vary by -5% to +5%



## SolarV GmbH

Am Kronberger Hang 2,65824 Schwalbach a.T



+49 (0)61969076877

info@solarv.de

www.solarv.de