



HPBC solar panel 200W 12V

Electrical characteristics

SKU	1180200
Maximum Power (Pmax)	200Wp
Voltage at Pmax (Vmp)	22.65V
Current at Pmax (Imp)	8.81A
Open-circuit Voltage (Voc)	26.15V
Short-circuit Current (Isc)	9.51A
Temperature coefficient of Voc	-0.270%/°C
Temperature coefficient of Isc	+0.048%/°C
Temperature coefficient of Power	-0.350%/°C
Normal operating cell Temperature	45 ± 2°C
Operating Temperature	-40 ~ +85°C
Maximum System Voltage	1000 VDC
Power Tolerance	0 ~ +3%
Junction box	IP67
Bypass diodes	3 pcs
Solar Cell	Mono 144 (4 × 36)
Connection cable and connector	4mm ² x 90cm, Solar Stecker (+/-)
Performance guarantee	25 years
Dimension (mm)	1180 × 770 × 30
Weight (kg)	9.99




Module diagram and characteristic curve




- HPBC solar cells
- 22.9% cell efficiency
- +3% Plus Tolerance Sorted
- reinforced aluminum frame
- TÜV Saar certified
- 25-year Product guarantee

I-V characteristics at different irradiances



I-V characteristics at different temperatures



*Measured at standard test conditions: irradiance 1.000W/m², air mass 1.5 spectrum, temperature 25°C
Electrical parameters may vary by -5% to +5%



SolarV GmbH

Am Kronberger Hang 2,65824 Schwalbach a.T



+49 (0)61969076877

info@solarv.de

www.solarv.de